

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings FX Intercoat

| INGREDIENTS | CAS NO | % | 8HR OEL |
|---|----------|-------|-----------|
| n-butyl acetate | 123-86-4 | 30-60 | 713 mg/m3 |
| methyl ethyl ketone | 78-93-3 | 20-30 | 445 mg/m3 |
| propylene glycol monomethyl ether acetate, alpha-isomer | 108-65-6 | <10 | 274 mg/m3 |
| n-butanol | 71-36-3 | <10 | - |



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S5

HEALTH HAZARD INFORMATION



| | |
|--------------------------------|--|
| Acute Health Effects: | Irritating to eyes and respiratory system. HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. |
| Chronic Health Effects: | Repeated exposure may cause skin dryness and cracking. * – limited evidence |

PRECAUTIONS FOR USE



| | |
|--|---|
| Appropriate engineering controls: | Local Exhaust Ventilation recommended. |
| Glasses: | Consider chemical goggles. |
| Gloves: | 1.PE/EVAL/PE 2.PVA 3.TEFLON |
| Respirator: | Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent) |
| Storage and Transportation: | Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. |
| Fire/Explosion Hazard: | HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. |

PROPERTIES



Liquid.
Does not mix with water.Highly flammable.

EMERGENCY



FIRST AID

| | |
|-----------------------------|--|
| Swallowed: | Give water (if conscious). URGENT MEDICAL ATTENTION. |
| Eye: | Wash with running water. |
| Skin: | Remove contaminated clothing. Wash with soap & water. |
| Inhaled: | Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention. |
| Fire Fighting: | Keep containers cool. Foam. Eliminate ignition sources. Consider evacuation. |
| Spills and Disposal: | Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. |

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 35-7099
 Print Date: 06/05/2014
 Issue Date: 20/05/2013