

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings Gla-StikZ

INGREDIENTS	CAS NO	%	8HR OEL
ethanol	64-17-5	50-100	1880 mg/m3
methanol	67-56-1	0-2.5	262 mg/m3
isopropanol	67-63-0	0-2.5	983 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S5

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.NEOPRENE 3.PVC

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.

Does not mix with water.

Floats on water.Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Supportive care.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together

o — May be stored together with specific preventions

+ — May be stored together



Chemwatch: 4656-97
 Print Date: 06/05/2014
 Issue Date: 01/01/2013