

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings Key Clear Hardener

INGREDIENTS	CAS NO	%	8HR OEL
hexamethylene diisocyanate	822-06-0	<0.5	0.02 mg/m3



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: III
 Poisons Schedule: S6

HEALTH HAZARD INFORMATION

Acute Health Effects:	Harmful by inhalation. Irritating to eyes. May cause SENSITISATION by inhalation and skin contact. Vapours may cause drowsiness and dizziness.
Chronic Health Effects:	Repeated exposure may cause skin dryness and cracking. * – limited evidence

PRECAUTIONS FOR USE

Glasses:	Safety Glasses. Consider chemical goggles.
Gloves:	1. PE/EVAL/PE 2. PVA 3. TEFLON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Flammable. Toxic smoke/fumes in a fire. Reacts with water.

PROPERTIES

Liquid.
Does not mix with water. Flammable.

EMERGENCY**FIRST AID**

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	For asthma inhale sympathomimetics Charcoal and cathartics for ingestion For corneal injury - mydriatics, analgesics.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 15-5663
 Print Date: 06/05/2014
 Issue Date: 01/01/2013