

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings High Definition Inter-Coat

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	10-25	350 mg/m3
sec-butyl acetate	105-46-4	>50	950 mg/m3
ethyl acetate	141-78-6	0-2.5	720 mg/m3
1,2,4-trimethyl benzene	95-63-6	0-2.5	-



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S5

HEALTH HAZARD INFORMATION



Acute Health Effects:	Harmful by inhalation and in contact with skin. Irritating to eyes and respiratory system. HARMFUL-May cause lung damage if swallowed.
Chronic Health Effects:	Repeated exposure may cause skin dryness and cracking. * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.VITON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire.
Environment:	Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.

PROPERTIES



Liquid.
Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 4673-96
 Print Date: 06/05/2014
 Issue Date: 01/01/2013