

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.


DNA Paints & Special Coatings 'HS' Primer Hardener (Med.)

INGREDIENTS	CAS NO	%	8HR OEL
hexamethylene diisocyanate polymer	28182-81-2	30-60	0.02 mg/m3
hexamethylene diisocyanate	822-06-0	<1	0.02 mg/m3
toluene	108-88-3	10-30	191 mg/m3
n-butyl acetate	123-86-4	10-30	713 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S6

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Irritating to eyes, respiratory system and skin.
 May cause SENSITISATION by inhalation and skin contact.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Glasses: Consider chemical goggles.

Gloves: 1. PE/EVAL/PE 2. PVA 3. TEFLON

Respirator: Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Take precautionary measures against static discharges.
 Dispose of this material and its container at hazardous or special waste collection point.
 Keep out of reach of children.
 Keep container in a well ventilated place.
 Keep away from food, drink and animal feeding stuffs.
 Keep away from sources of ignition. No smoking.

PROPERTIES



Liquid.
 Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. For asthma inhale sympathomimetics Charcoal and cathartics for ingestion For corneal injury - mydriatics, analgesics.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together

0 — May be stored together with specific precautions



Chemwatch: 4732-41
 Print Date: 06/05/2014
 Issue Date: 16/04/2014

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings HS Primer Hardener Fast

INGREDIENTS	CAS NO	%	8HR OEL
hexamethylene diisocyanate polymer	28182-81-2	30-60	0.02 mg/m3
hexamethylene diisocyanate	822-06-0	<1	0.02 mg/m3
toluene	108-88-3	10-30	191 mg/m3
n-butyl acetate	123-86-4	10-30	713 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S6

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Irritating to eyes and skin.
 May cause SENSITISATION by inhalation and skin contact.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

May cause harm to the unborn child.
 Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Safety Glasses.
 Consider chemical goggles.

Gloves:

1. PE/EVAL/PE 2. PVA 3. TEFLON

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 Reacts with water.

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. For asthma inhale sympathomimetics Charcoal and cathartics for ingestion For corneal injury - mydriatics, analgesics.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X — Must not be stored together
 0 — May be stored together with specific precautions
 + — May be stored together



Chemwatch: 23-5365
 Print Date: 06/05/2014
 Issue Date: 01/01/2013

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings 'HS' Primer Hardener (Slow)

INGREDIENTS	CAS NO	%	8HR OEL
hexamethylene diisocyanate polymer	28182-81-2	30-60	0.02 mg/m3
hexamethylene diisocyanate	822-06-0	<1	0.02 mg/m3
xylene	1330-20-7	10-30	350 mg/m3
n-butyl acetate	123-86-4	10-30	713 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S6

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and in contact with skin. Irritating to eyes, respiratory system and skin. May cause SENSITISATION by inhalation and skin contact. Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Glasses: Consider chemical goggles.

Gloves: 1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator: Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.

HIGHLY FLAMMABLE.

Vapours/gas heavier than air.

PROPERTIES



Liquid.
Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. For asthma inhale sympathomimetics Charcoal and cathartics for ingestion For corneal injury - mydriatics, analgesics.
Fire Fighting:	Foam. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.
Spills and Disposal:	Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Chemwatch: 4732-43
 Print Date: 06/05/2014
 Issue Date: 16/04/2014