

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings Ice Chrome

INGREDIENTS	CAS NO	%	8HR OEL
n-butyl acetate	123-86-4	<45	713 mg/m3
ethyl acetate	141-78-6	<50	720 mg/m3
amyl methyl ketone	110-43-0	<8	233 mg/m3
ethylbenzene	100-41-4	<2.5	434 mg/m3




UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: Not Applicable

HEALTH HAZARD INFORMATION


Acute Health Effects:	Irritating to eyes. HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.
Chronic Health Effects:	Repeated exposure may cause skin dryness and cracking. * – limited evidence

PRECAUTIONS FOR USE


Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PVA
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire.

PROPERTIES

EMERGENCY

FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS


x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 4992-58
 Print Date: 06/05/2014
 Issue Date: 01/01/2013