

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings Basecoat Reducer (Medium)

INGREDIENTS	CAS NO	%	8HR OEL
methyl ethyl ketone	78-93-3	50-60	445 mg/m3
n-butyl acetate	123-86-4	10-15	713 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	0-5	274 mg/m3
xylene	1330-20-7	<4.5	350 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S5

HEALTH HAZARD INFORMATION



Acute Health Effects:	Irritating to eyes and respiratory system. HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.
Chronic Health Effects:	Repeated exposure may cause skin dryness and cracking. * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.TEFLON 3.PVA
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 20-7505
 Print Date: 06/05/2014
 Issue Date: 01/01/2013

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

DNA Paints & Special Coatings Basecoat Reducer (Slow)

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	10-30	191 mg/m3
n-butyl acetate	123-86-4	10-30	713 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	0-10	274 mg/m3
xylene	1330-20-7	0-10	350 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: Not Applicable
 Packing Group: II
 Poisons Schedule: S5

HEALTH HAZARD INFORMATION


Acute Health Effects:

Harmful by inhalation and if swallowed.
 Irritating to eyes and skin.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE


Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1. PE/EVAL/PE 2. PVA 3. TEFLON

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
 Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 4732-89
 Print Date: 06/05/2014
 Issue Date: 01/01/2013