

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Reducer FX Fast/Medium (2K)

INGREDIENTS	CAS NO	%	8HR OEL
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	10-30	274 mg/m3
xylene	1330-20-7	10-30	350 mg/m3
n-butyl acetate	123-86-4	10-30	713 mg/m3



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5

PROPERTIES

Liquid. Does not mix with water. Flammable.

EMERGENCY**FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together

HEALTH HAZARD INFORMATION

Acute Health Effects: Harmful by inhalation and in contact with skin. Irritating to eyes and skin. Vapours may cause drowsiness and dizziness.

Chronic Health Effects: Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PRECAUTIONS FOR USE

Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: 1.VITON 2.PE/EVAL/PE 3.PVA

Respirator: Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard: Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

Environment: Harmful to aquatic organisms.



Chemwatch: 4732-47
 Print Date: 27/11/2015
 Issue Date: 14/09/2015

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Reducer FX Slow (2K)

INGREDIENTS	CAS NO	%	8HR OEL
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	10-30	274 mg/m3
ethylene glycol monobutyl ether acetate	112-07-2	0-10	133 mg/m3
xylene	1330-20-7	10-30	350 mg/m3
n-butyl acetate	123-86-4	10-30	713 mg/m3



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5

PROPERTIES

Liquid. Does not mix with water. Flammable.

EMERGENCY**FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.

HEALTH HAZARD INFORMATION**Acute Health Effects:**

Harmful by inhalation and in contact with skin.
 Irritating to eyes and skin.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE**Appropriate engineering controls:**

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.VITON 2.PE/EVAL/PE 3.PVA

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

Environment:

Harmful to aquatic organisms.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together



Chemwatch: 4732-48
 Print Date: 27/11/2015
 Issue Date: 14/09/2015

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Reducer FX High Flow (2K)

INGREDIENTS	CAS NO	%	8HR OEL
ethylene glycol monobutyl ether acetate	112-07-2	10-30	133 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	30-60	274 mg/m3
xylene	1330-20-7	10-30	350 mg/m3



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5

PROPERTIES

Liquid. Does not mix with water. Flammable.

EMERGENCY**FIRST AID**

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together
 0 — May be stored together with specific preventions
 + — May be stored together

HEALTH HAZARD INFORMATION

Acute Health Effects: Harmful by inhalation and in contact with skin. Irritating to eyes and skin.

PRECAUTIONS FOR USE

Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1. PE/EVAL/PE 2. PVA 3. TEFLON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.
Environment:	Harmful to aquatic organisms.



Chemwatch: 41-7768
 Print Date: 27/11/2015
 Issue Date: 11/09/2015