



Technical Data Sheet

Date of issue	Revision Date	Version
18/09/09	26/05/14	1.1
Product Code	Product Name	
CA04-	Wax & Grease Remover	

DNA[®] Wax & Grease Remover is an extremely heavy duty cleaning solution specifically designed for initial surface preparation before repairing any coated surfaces.

Wax & Grease Remover removes surface silicones, waxes, insects and road film, tar, dirt, grease, and pinstripe adhesives and is ready for use. Suitable for bare metal surfaces, unsanded substrates, OEM finishes and cured repainted finishes.

Wax & Grease Remover *Always check that you have the latest TDS*



MSDS

Observe all safety precautions in relation to this product's Material Safety Data Sheet



SAFETY

Always wear appropriate safety clothing, gloves, breathing & apparatus

STORAGE

Several years in cool, dry conditions

APPLICATION GUIDE:



1. Always test on a small inconspicuous area for compatibility.
2. Wipe dry with clean cloth or blow dry with deionised air.
3. Soak a clean cloth with Wax & Grease Remover.
4. Treat only one small area at a time using a 'two-rag wipe' technique, wet one rag with Wax & Grease Remover and wipe the entire surface area with it and DO NOT allow to evaporate from the surface.
5. Use the second rag to immediately wipe the wet Wax & Grease Remover from the surface BEFORE it evaporates! Allowing Wax & Grease Remover to dry on the surface without wiping re-deposits the surface grime as the Wax & Grease Remover dries.
6. Change cloths often, never use dirty cloths.
7. Do not spread contaminants being removed over other areas being cleaned. Any residue left may later discolour or cause stains.
8. When cleaning deep, narrow joints wrap the cleaning cloth around a clean narrow metal blade or putty knife to enable force to be applied to the surface being cleaned.
9. Clean only as much area as can be sealed in one hour. If cleaned areas are again exposed to any contamination or weather, the surface must be cleaned again.
10. Change cloths often, never use dirty cloths. It is important to thoroughly clean the surface before any sanding operation. Sanding would grind contaminants into the surface.
11. Close container tightly after use. This prevents the cleaner from evaporating and losing its effectiveness.

For further information refer to the DNA[®] Training Manual, Wax & Grease Remover TDS or contact DNA[®] Technical Support. Phone: +61 (03) 9764 2088

Note: Custom painting can be difficult. All products should be fully tested prior to commencing any job to determine suitability, final finish and overall appearance. All information and data provided by DNA[®] is given in good faith and intended to be a general guide only. DNA[®] shall not accept liability as a result of any failure or lack of expertise on the part of the applicator, condition of substrates, lack of, or incorrect preparation, use of incompatible materials, equipment failure or use of incorrect equipment or any other reason beyond the control of DNA[®] and further offers no warranties of whatever nature express or implied as to merchantability or fitness for a particular use or purpose and shall not accept liability for any specific or consequential damage as a result of using these products unless otherwise agreed to in writing. Should a product be defective, DNA[®] shall replace the defective product, or, at its sole discretion refund the purchase price.

The trademarks used herein are either trademarks or registered trademarks in Australia and/or other countries and owned or used under license by Vincent River Pty Ltd. Copyright © 2005-2014 Vincent River Pty Ltd. All rights reserved.