

WORK PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Replenish Wax

| INGREDIENTS | CAS NO | % | 8HR OEL |
|---------------------------|---------------|------|-----------|
| white spirit | 8052-41-3. | 5-50 | 790 mg/m3 |
| petroleum distillates HFP | 64742-48-9. | 5-50 | - |
| aminofunctional additive | Not Available | 5-50 | - |
| polydimethylsiloxane | 63148-62-9 | 5-50 | - |

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**

PROPERTIES

Liquid.
Mixes with water. Combustible.

EMERGENCY**FIRST AID**

| | |
|-----------------------------|---|
| Swallowed: | Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol. |
| Eye: | Wash with running water. |
| Skin: | Remove contaminated clothing. Wash with soap & water. |
| Inhaled: | Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention. |
| Advice To Doctor: | Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. |
| Fire Fighting: | Water spray/ fog. |
| Spills and Disposal: | Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. |

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together
 0 — May be stored together with specific precautions
 + — May be stored together

HEALTH HAZARD INFORMATION**Acute Health Effects:**

Irritating to skin.
HARMFUL-May cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.
* – limited evidence

PRECAUTIONS FOR USE**Appropriate engineering controls:**

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.NEOPRENE 2.VITON 3.BUTYL

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.

